

NOVASTOR CORPORATION

NovaBACKUP Best Practices - Client

© 2012 NovaStor, all rights reserved. All trademarks are the property of their respective owners. Features and specifications are subject to change without notice. The information provided herein is provided for informational and planning purposes only.

Introduction

NovaStor recommends the following best practices in setting up and running NovaBACKUP.

Offsite

- Use offsite backup with critical data to help avoid a single point of failure.
- Select only critical information to back up offline to minimize the amount of data being transferred, and increase overall performance.
- (xSP) To enable FastBIT transfers for a file, that file must have at least 2 copies previously backed up on the server.
- (xSP) To enhance FastBIT, make sure the Work directory has free disk space totaling at least 3x the total amount of data you want to transfer.
- Make sure ports 308 and 3817 are open in both directions.

Local

- Create a rotation schedule as opposed to running each backup manually to increase the stability and performance of your backups.
- Schedule weekly Full Backups and daily Incremental Backups to maximize your rotation's efficiency.
- Use more than one device for your backups, ideally alternating between devices regularly to avoid a single point of failure.
- Schedule jobs to run after office hours to ensure that all information is current and that the software will not interfere with normal procedures while it runs.

Disaster Recovery

- Update Disaster Recovery (DR) images monthly. More frequent images are generally inefficient and less frequent images can be outdated.
- DR Images can be scheduled to run monthly by scheduling it to run on a single day (for example, Saturday) and setting it to run only every 4th day. This tells the software to run a DR Image every 4th Saturday.
- Ideally, keep 2-3 DR images stored separately to avoid a single point of failure.
- Create a new DR image any time new hardware or software is installed to minimize compatibility issues.
- If your machine requires a hardware replacement, make sure any new hardware is as similar as possible (preferably identical) to minimize compatibility issues.
- Store at least one recent DR image at an offsite location to protect your data in the event of a serious disaster, such as a flood or fire at your business.
- If backing up to a removable device, keep one device onsite and one device offsite, and swap these weekly. You will always have the previous week's data offsite in case of a major disaster.
- Create DR boot disks for each device – one boot disk will not work across all devices.

Plugins

- If using Exchange 2007, place the NovaBACKUP Exchange 2007 plugin into the BIN folder of the Exchange directory. Set the NovaBACKUP service to run as a Domain Administrator with credentials that can be recognized by Exchange/SQL.
- Our SQL plugin supports MSSQL only, will not work with MySQL or Pervasive.
- Only one instance of SQL can be installed and running, other instances will cause a conflict.

Restores

- Stop any non-essential services when running a restore to increase overall stability during the restore.
- Ensure that the hardware configuration has not changed, or is as similar as possible to the configuration when the data was backed up.
- The “Restore File to Alternate Location” setting allows you to restore files without overwriting existing information.

Logging

- Logging Options can be found under Settings > Notification.
- Set logging to Summary (default) unless you are troubleshooting an issue with backing up/restoring.
- Email logs to monitor your backup jobs remotely.